

# United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/940,767	08/27/2001	Arnold M. Lund	020366-074100US	6793
20350	7590 02/02/2005		EXAMINER	
	ND AND TOWNSEND	YANG, CLARA I		
	TWO EMBARCADERO CENTER EIGHTH FLOOR SAN FRANCISCO, CA 94111-3834			PAPER NUMBER
SAN FRAN				2635
			DATE MAILED: 02/02/2005	

Please find below and/or attached an Office communication concerning this application or proceeding.

·		(A				
	Applicati n N .	Applicant(s)				
Offic Action Summan	09/940,767	LUND, ARNOLD M.				
Offic Action Summary	Examiner	Art Unit				
TI MAN INC DATE AND	Clara Yang	2635				
The MAILING DATE of this communication app Period for Reply	ars on the cover shet with the c	corresp ndenc address				
A SHORTENED STATUTORY PERIOD FOR REPLY THE MAILING DATE OF THIS COMMUNICATION.  - Extensions of time may be available under the provisions of 37 CFR 1.13 after SIX (6) MONTHS from the mailing date of this communication.  - If the period for reply specified above is less than thirty (30) days, a reply of NO period for reply is specified above, the maximum statutory period wown is a specified above. The maximum statutory period wown is a specified above. The maximum statutory period wown is a specified above. The maximum statutory period wown is a specified above. The maximum statutory period wown is a specified above. The maximum statutory period wown is a specified above. The maximum statutory period wown is a specified above. The maximum statutory period will be statuted as a specified above. The maximum statutory period wown is a specified above. The maximum statutory period wown is a specified above. The maximum statutory period wown is a specified above. The maximum statutory period wown is a specified above and specified above. The maximum statutory period wown is a specified above and specified above are specified above. The maximum statutory period wown is a specified above and specified above are specified above. The maximum statutory period wown is a specified above and specified above are specified above. The maximum statutory period wown is a specified above and specified above are specified above. The maximum statutory period wown is a specified above and specified above are specified above. The maximum statutory period wown is a specified above and specified above are specified above. The maximum statutory period was a specified above and specified above are specified above. The maximum statutory period was a specified above and specified above are specified above and specified above are specified above are specified above and specified above are specified abov	16(a). In no event, however, may a reply be tin within the statutory minimum of thirty (30) day fill apply and will expire SIX (6) MONTHS from cause the application to become ABANDONE	nely filed s will be considered timely. the mailing date of this communication. D (35 U.S.C. § 133).				
Status						
1)⊠ Responsive to communication(s) filed on 23 Se	eptember 2004.					
_						
3) Since this application is in condition for allowance except for formal matters, prosecution as to the merits is						
closed in accordance with the practice under E	closed in accordance with the practice under Ex parte Quayle, 1935 C.D. 11, 453 O.G. 213.					
Disposition of Claims						
<ul> <li>4)  Claim(s) 1-3,5-7,9-11,13,15,17,19 and 21-25 is/are pending in the application.</li> <li>4a) Of the above claim(s) is/are withdrawn from consideration.</li> <li>5)  Claim(s) is/are allowed.</li> <li>6)  Claim(s) 1-3,5-7,9-11,13,15,17,19 and 21-25 is/are rejected.</li> <li>7)  Claim(s) is/are objected to.</li> <li>8)  Claim(s) are subject to restriction and/or election requirement.</li> </ul>						
Application Papers						
9)☐ The specification is objected to by the Examiner						
10)⊠ The drawing(s) filed on <u>27 August 2001</u> is/are: a)⊠ accepted or b)□ objected to by the Examiner.						
Applicant may not request that any objection to the o	drawing(s) be held in abeyance. See	e 37 CFR 1.85(a).				
Replacement drawing sheet(s) including the correction						
11) The oath or declaration is objected to by the Exa	aminer. Note the attached Office	Action or form PTO-152.				
Priority under 35 U.S.C. § 119						
<ul> <li>12) Acknowledgment is made of a claim for foreign and All b) Some * c) None of:</li> <li>1. Certified copies of the priority documents</li> <li>2. Certified copies of the priority documents</li> <li>3. Copies of the certified copies of the priority application from the International Bureau</li> <li>* See the attached detailed Office action for a list of</li> </ul>	have been received. have been received in Application ty documents have been received (PCT Rule 17.2(a)).	on No ed in this National Stage				
Attachment(s)  1) X Notice of References Cited (PTO-892)		(DTC 110)				
2) Notice of Praftsperson's Patent Drawing Review (PTO-948)	4)  Interview Summary Paper No(s)/Mail Da					
3) Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08) Paper No(s)/Mail Date		atent Application (PTO-152)				
Patent and Trademark Office						

Application/Control Number: 09/940,767

Art Unit: 2635

#### **DETAILED ACTION**

### Response to Arguments

1. Applicant's arguments filed on 23 September 2004 with respect to claims 1 – 3, 5 – 7, 9 – 11, 13, 15, 17 – 19, 22 and 23 have been fully considered but they are not persuasive.

On page 8, the applicant argues that Gorday and LaPorta fail to teach the steps of determining that a recipient of a page (i.e., "pagee") failed to respond to a page within a predetermined time period and converting the received page to a message that is communication mode agnostic. On the contrary, Gorday teaches a method comprising the steps of: (a) system controller 102 sending the page wirelessly to the intended PSU 106 (i.e., "pager") via transmitter/receiver 103 (see Fig. 1 and Col. 5, lines 11 - 16); (b) system controller 102 determining if a predetermined time limit for a response, such as an acknowledgment (ACK) or a non-acknowledgment (NACK), from PSU 106 has been exceeded (see Fig. 4, step 416); and (c) processing system 204 of system controller 102 storing the page message when the time limit for a response and the number of retransmissions have been exceeded; and (d) notifying PSU 106 via a second message (or activating a message-waiting indicator) that a first message is being stored (see Fig. 4, steps 416, 430, and 424; and Col. 10, lines 14 - 25 and 46 - 55). Per Gorday, PSU 106 is one of several types of devices, including two-way pagers (see Col. 5, lines 34 – 35). Though Gorday discloses that alternate means of delivery, such as voice mail or email, can be used when a page is undeliverable (see Col. 4, lines 53 - 55, is silent on the step of storing the first message in a communication agnostic format. In an analogous art, LaPorta teaches in Figs. 7 and 8 that when a subscriber S 200 sends a message to recipients R1 202, R2 204, and R3 206 via batch server 208, batch server 208 forwards the message to messaging server 210, which contacts the user agent of subscriber 200 (i.e., UA-S 212) (see Col. 14, lines 41 - 62). Messaging

server 210 contacts the user agents of the message recipients to determine the location of their corresponding messaging devices, the format in which they wish to received the message, and their status (see Col. 14, lines 60 – 67 and Col. 15, lines 1 – 12). The user agent of recipient R3 (UA-R3) responds that its pager is off and that the message should be forwarded to message storage server 224 (see Col. 15, lines 15 – 16). Message storage server 224 (d) stores the message, and UA-R3 (e) sends a retrieval ID, thereby activating a message-waiting indicator to R3, when R3 powers on (see Col. 15, lines 44 – 51). Message storage server 224 must store messages in a communication mode agnostic format because distribution server 116 is responsible for delivering messages to their final destination in the proper format by executing a direct paging algorithm or by routing the messages to a translator prior to transmission (see Col. 11, lines 28 – 35). Thus, Gorday, as modified by LaPorta, does teach the limitations of claim 1.

The applicant further states "Applicant can find no mention in [Gorday, Col. 3, lines 60 – 65 and Col. 5, lines 11 - 16] or the remaining disclosure of Gorday of converting the page received from the pagor to a message at a location other than the location of the pager." Regarding the section in Col. 3, lines 60 – 65, Gorday teaches that an outbound alphanumeric message intended for portable subscriber unit (PSU) 106 (i.e., a pager) is entered at messaging terminal 122 and that a voice page message is entered from telephone 101. Per Gorday, an example of an outbound alphanumeric message intended for PSU 106 is an alphanumeric page entered at messaging terminal 122. Messaging terminal 122 and telephone 101 are at a first location. In Col. 5, lines 11 – 16, Gorday discloses that system controller 102 encodes (i.e., converts the pages into messages) and schedules the pages for transmission to a plurality of PSU 106 located at a second location. As shown in Fig. 1, system controller 102 is at a location

Art Unit: 2635

other than the location of PSU 106; hence Gorday does teach the limitation of "converting the page to a message away from the second location".

## Claim Rejections - 35 USC § 103

- 2. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
  - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 3. Claims 1 3, 5 7, 9 11, 13, 15, 17 19, and 21 25 are rejected under 35 U.S.C. 103(a) as being unpatentable over Gorday (US 5,703,570) in view of LaPorta (US 5,974,300).

Referring to claims 1, 6, 7, 10, 15, and 18, Gorday teaches a paging method wherein system controller 102 performs the steps of: (a) receiving a message intended for a portable subscriber unit (PSU) 106 from a remote sender (i.e., "pagor") at a first location via telephone 101, facsimile machine 120, or messaging terminal 122 as required in claims 10 and 18 (see Col. 3, lines 50 - 55 and 60 - 65); (b) sending the page wirelessly to the intended PSU 106 (i.e., "pager") via transmitter/receiver 103 as required in claims 1, 10, and 18 (see Fig. 1 and Col. 5, lines 11 - 16); (c) determining if a predetermined time limit for a response, such as an acknowledgment (ACK) or a non-acknowledgment (NACK), from PSU 106 has been exceeded as required in claims 1, 10, and 18 (see Fig. 4, step 416 and Col. 10, lines 14 - 32 and 46 - 52); (d) converting the outbound message received from a message input device to a page message as required in claims 10 and 18 (see Col. 3, lines 60 - 65 and Col. 5, lines 11 - 16); (e) storing the page message via processing system 204 when the time limit for a response and the number of retransmissions have been exceeded (i.e., a predetermined criterion has been satisfied) as

Art Unit: 2635

required in claims 1 and 18 (see Fig. 4, steps 416, 430, and 424; and Col. 10, lines 14 - 25 and 46 -55); and (f) notifying PSU 106 via a second message (or activating a message-waiting indicator) that a first message is being stored as required in claim 1 (see Fig. 4, steps 416, 430, and 424; and Col. 10, lines 14 - 25 and 46 - 55). Per Gorday, PSU 106 is one of several types of devices, including two-way pagers (see Col. 5, lines 34 - 35). Gorday also imparts that when the intended PSU 106 receives an outbound message transmitted by system controller 102, a user (or "pagee") can use PSU 106 to generate and transmit an inbound response back to system controller 102. System controller 102's message handler function identifies the inbound response as having been generated by the user specifically in response to the outbound message and generates another message that is sent to the originator (i.e., "pagor") of the outbound message to notify the originator that the outbound message has been acknowledged and responded to by PSU 106. (See Col. 6, lines 35 - 52.) In order for a user to respond to the originator's outbound message via PSU 106, Gorday's method further includes the step of system controller 102 (g) storing information relating to the originator's communication mode that can be used to send a response to the originator via system controller 102 as required in claim 6. Though Gorday discloses that alternate means of delivery, such as voice mail or email, can be used when a page is undeliverable (see Col. 4, lines 53 - 55, is silent on the steps of (1) storing the first message in a communication agnostic format (as called for in claim 1) and (2) storing information relating to a plurality of communication modes for the pagor that the pagee can use when returning the page (as called for in claims 7, 10, 15, and 18).

In an analogous art, LaPorta's method for sending a page to a recipient (or "pagee") comprises the steps of: (a) two-way message network 14 receiving a page from pager 50a, which is at a first location (see Fig. 3 and Col. 5, lines 53 – 62); (b) two-way message network 14

Art Unit: 2635

sending a page via air interface 57a to pager 58, which is at a second location (see Col. 5, lines 53 - 62); and (c) user agent 50 expanding or converting the page into a full message prior to sending the page (see Col. 6, lines 3 - 10). LaPorta also teaches in Figs. 7 and 8 that when a subscriber S 200 sends a message to recipients R1 202, R2 204, and R3 206 via batch server 208, batch server 208 forwards the message to messaging server 210, which contacts the user agent of subscriber 200 (i.e., UA-S 212) (see Col. 14, lines 41 - 62). Messaging server 210 contacts the user agents of the message recipients to determine the location of their corresponding messaging devices, the format in which they wish to received the message, and their status (see Col. 14, lines 60 – 67 and Col. 15, lines 1 – 12). The user agent of recipient R3 (UA-R3) responds that its pager is off and that the message should be forwarded to message storage server 224 (see Col. 15, lines 15 - 16). Message storage server 224 (d) stores the message, and UA-R3 (e) sends a retrieval ID, thereby activating a message-waiting indicator to R3, when R3 powers on (see Col. 15, lines 44 - 51). Because Gorday specifies distribution server 116 is responsible for delivering messages to their final destination in the proper format by executing a direct paging algorithm or by routing the messages to a translator prior to transmission, message storage server 224 must store messages in a communication mode agnostic format as called for in claim 1 (see Col. 11, lines 28 - 35). LaPorta further teaches the step of (f) a sender's user agent storing information relating to format and filtering/forwarding criteria (or communication mode) for the page recipients to use when returning the page (see Col. 6, lines 18 - 25; Col. 7, lines 18 - 40; Col. 8, lines 17 – 18; Col. 11, lines 28 – 42; and Col. 16, lines 5 – 30). Per LaPorta, the originator's message includes an array of reply-to addresses (see Col. 14, lines 41 - 46). In light that a subscriber 40's user agent is able to forward messages as specified by the subscriber and that a subscriber can have a plurality of reply-to addresses, the user agent must store a plurality of

communication modes for a subscriber. Consequently, LaPorta teaches the step of storing information relating to a plurality of communication modes for the sender that the recipient can use when returning the page (as called for in claims 10 and 18).

Therefore, it would have been obvious to one having ordinary skill in the art at the time the invention was made to modify the method of Gorday as taught by LaPorta because storing an undeliverable message in a communication mode agnostic supports multicasting without the user having to specify the communication mode and enables a user to send a message to other message devices other than pagers (see LaPorta, Col. 2, lines 58 – 65; Col. 5, lines 53 – 62; and Col. 16, lines 47 – 49). In addition, storing a plurality an originator's communication modes can be used when a user responds to an originator's message improves the likelihood of the originator receiving the responses, thus improving radio communication system 100's performance.

Regarding claim 2, Gorday's system controller 102 includes an outbound message memory 208 for storing pending and undeliverable messages for PSUs 106 (see Fig. 2; Col. 5, lines 60 – 63; Col. 6, lines 24 – 30; and Col. 10, lines 14 – 20).

Regarding claims 3 and 11, as described above in claims 1 and 10, Gorday's radio communication system 100 enables PSUs 106 to receive messages from telephones, facsimile machines, and messaging terminals, which are devices other than pagers. This is accomplished by Gorday's system controller 102, which (1) receives messages from telephones, facsimile machines, and messaging terminals, (2) encodes the outbound messages intended for PCU 106, (3) stores a queue of the encoded outbound messages in message memory 208, (4) transmits the outbound messages to PSUs 106, and (5) stores the undeliverable outbound messages in message memory 208 (see Fig. 4, steps 408 and 424; Col. 5, lines 11 – 16; Col. 6, lines 24 – 30; and

Col. 10, lines 14 - 25 and 46 - 52). Consequently, Gorday's system controller 102 and transmitter/receiver 103 are understood to form a unified messaging system.

Regarding Claims 5 and 13, Gorday omits teaching the step of system controller 102 receiving from a page sender (i.e., the "originator" or "pagor") at least one of a plurality of predetermined messages that is to be sent to an intended PSU 106.

Per LaPorta, two-way wireless messaging system 10 supports various types of messages, such as pre-canned or predetermined messages (see Col. 13, lines 55 – 67 and Col. 14, lines 1 – 20). Referring to Figs. 7 and 8, LaPorta teaches a sender S 200 sending message PG2BS-NEW, which is one of a plurality of pre-canned messages since user agent UA-S 212 performs the message expansion function prior to forwarding the message messaging server 210 (see Col. 14, lines 60 – 65).

Therefore, it would have been obvious to one having ordinary skill in the art at the time the invention was made to modify the method of Gorday as taught by LaPorta because the step of transmitting at least one of a plurality of pre-canned messages enables the sender (i.e., "pagor") to send messages with limited input, thereby making message generation easy and practical, especially when the messaging device has little or no input means (see LaPorta, Col. 13, lines 47 – 52).

Regarding claims 9, 17, and 21, Gorday's processing system 204, as shown in Fig. 2, includes a conventional computer system 212 and mass storage media 214, wherein the functions of processing system 204 are executed by computer system 212 and controlled by a set of program instructions stored in mass storage media 214 (see Col. 7, lines 2 – 14 and 22 – 30).

Regarding claim 19, as discussed in claim 6, in order for a user (i.e., "pagee") to respond to an originator's (i.e., "pagor") outbound message via PSU 106, system controller 102 must

store information relating to the originator's communication mode that can be used by PSU 106 to send a response to the originator. Consequently, Gorday's method further includes the steps of: (a) system controller 102 (i.e., "the unified messaging system") receiving PSU 106's response to a received outbound message; (b) system controller 102's message handler function identifying the inbound response as having been generated by the user specifically in response to the outbound message and generating another message to be sent to the originator for notifying the originator that the outbound message has been acknowledged and responded to by PSU 106; and (c) system controller 102's message handler function retrieving the originator's communication mode information from memory and routing the new outbound message according to the retrieved information. (See Col. 6, lines 7 – 16 and 35 – 52.)

4. Claims 22 – 25 are rejected under 35 U.S.C. 103(a) as being unpatentable over Gorday (US 5,703,570) in view of LaPorta (US 5,974,300) as applied to claims 1, 10, and 18 above, and further in view of DeLuca (US 5,258,751).

Gorday and LaPorta are silent that activating the message-waiting indicator comprises activating a sensory indicator, such as a light indicator, an audible indicator, or a tactile indicator.

In an analogous art, DeLuca's selective call receiver (SCR) 200, as shown in Fig. 2, comprises audible alert 210, visual indicator 211, and tactile alert 212 that function as message-waiting indicators (see Col. 4, lines 42 – 49 and Col. 8, lines 21 - 26). SCR 200 is also able to indicate unread messages via display 208 (see Fig. 7C and Col. 8, lines 26 – 30).

Therefore, it would have been obvious to one having ordinary skill in the art at the time the invention was made to modify PSU 106 of Gorday and LaPorta as taught by DeLuca

because a PSU 106 having three different types of message-waiting indicators ensure that a user is notified of unread messages.

5. Claims 23 - 25 are rejected under 35 U.S.C. 103(a) as being unpatentable over Gorday (US 5,703,570) in view of LaPorta (US 5,974,300) as applied to claims 1, 10, and 18 above, and further in view of Kudoh (US 5,726,642).

Gorday and LaPorta are silent that activating the message-waiting indicator comprises activating a sensory indicator.

In an analogous art, Kudoh teaches that alarm portion 10, which constitutes a loudspeaker, performs call alarms (i.e., a new message alarm and a non-read alarm) that are different depending on whether or not there is a non-read message (see Col. 4, lines 28 – 37). Because the ear is a sensory organ, alarm portion 10 is considered to be a sensory indicator.

Therefore, it would have been obvious to one having ordinary skill in the art at the time the invention was made to modify PSU 106 of Gorday and LaPorta as taught by Kudoh because a user is able determine presence of unread messages without having to look at PSU 106 if the message-waiting indicator is an alarm portion 10.

#### \*\*\*

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Clara Yang whose telephone number is (571) 272-3062. The examiner can normally be reached on 8:30 AM - 7:00 PM, Monday - Thursday.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Michael Horabik can be reached on (571) 272-3068. The fax phone number for the organization where this application or proceeding is assigned is 703-872-9306.

Application/Control Number: 09/940,767

Art Unit: 2635

Page 11

Information regarding the status of an application may be obtained from the Patent

Application Information Retrieval (PAIR) system. Status information for published applications

may be obtained from either Private PAIR or Public PAIR. Status information for unpublished

applications is available through Private PAIR only. For more information about the PAIR

system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private

PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

CY

BRIAN ZIMMERMAN PRIMARY EXAMINER